



ANALYTIC SYSTEMS

Power Conversion Solutions

#207 12448 82nd Ave.
Surrey, BC V3W 3E9 CANADA

+1 (604) 543-7378 · phone
1-800-668-3884 · toll free
+1 (604) 543-7354 · fax

www.analyticsystems.com



Benefits

- Ultra-Quiet
- Power sensitive electronics without interference
- Rugged & Reliable
- Ensure years of safe and trouble free operation

Applications

- Marine / Automotive / RV
- Electric Utilities and Substations
- Telecom Power Plants
- Manufacturing Locations
- Steel Mills
- Military Applications (COTS)
- Industrial Controls
- OEM Applications
- Solar / Alternative Power Systems
- Fuel Cells

AC/AC Frequency Converters

FCA250 Series Frequency Converters

Description

The FCA250 Series is a highly compact AC/AC frequency converter. Suitable for a wide range of applications, the FC 250 features full electronic protection, high efficiency and low output noise.

Well established design techniques are used to ensure high reliability. The unit is conduction/convection cooled.

Extended operating temperature (-40 to +65°C) is available.

Features

- Convection cooled
- Compact size, light weight
- Sinusoidal wave shape
- Modular design, light weight
- Sinusoidal wave shape
- 250VA of output power
- Full electronic protection
- Telecom quality
- Field-proven design topology

FC250 Series AC/AC Frequency Converters

Specifications

Input Voltage	115 or 230VAC, 48 ... 410Hz +/-20% are standard Other inputs available: please consult factory
Input Protection	Thermal fuse, Inrush current limiting, Reverse polarity protection
Isolation	2250VDC input to chassis / 2250 VDC input to output / 2250VDC output to chassis
Output Voltage	115V / 60Hz / 2.2A or 115V / 400Hz / 2.2A or 230V / 50Hz / 1.1A continuous with grounded neutral Isolated floating output optional
Wave Form	Sinusoidal
Total Harmonic Distortion	Less than 5% at full load
Efficiency	Min 78% at full load
Line Regulation	Maximum 0.5%
Load Regulation	Max. \pm 6% from 10% load to full load
Output Protection	Current limiting with short circuit protection; Thermal shutdown with automatic recovery in case of continuous overload or insufficient airflow
EMI	Meets EN 55022 Class B
Load Crest Factor	Maximum 3.0 at 90% load
Operating Temperature Range	0°C to +50°C
Temperature Drift	0.05% per °C over operating temperature range
Dimensions	5.3" x 5" x 15.5" vented case (H x W x L)
Connections	Input: Compression-type terminal Output: Standard AC receptacle
Weight	9 pounds (4 kg)
Safety	Compliance to IEC950, CSA C22.2 No. 950 and UL 1950 Please contact factory for approval status for the requested input/output configuration

Warranty: Twelve months subject to application within good engineering practice

Enhancements to these general specifications can be accommodated upon request

Designed to meet common approval requirements. Specifications Subject to Change Without Notice

Designed and Manufactured in Canada

Available From:



ANALYTIC SYSTEMS

Quality since 1976

#207 12448 82nd Ave.
Surrey, BC V3W 3E9 CANADA
+1 (604) 543-7378 • phone
1-800-668-3884 • toll free
+1-604-543-7354 • fax
www.analyticsystems.com

© 2003 Analytic Systems Ware Ltd. (1993)